

Material Safety Data Sheet HORIZON-SPT

Product Name:HORIZON-SPT

HMIS HEALTH.....3
HMIS FLAMMABILITY.....2
HMIS REACTIVITY.....0
HMIS PROTECTION.....B

SECTION I – IDENTIFICATION

COMPANY NAME:.....ENERGY INTERMEDIATES, INC.
P.O. Box 50010
Midland, TX. 79710
COMPANY PHONE:.....(432)570-6799
EMERGENCY NUMBER.....(432)570-6799
EFFECTIVE DATE.....June, 2013
CHEMICAL FAMILY.....General Purpose
CAS NUMBER.....Proprietary

SECTION II – HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENT	PERCENT	CAS NUMBER	TLV
Methyl Alcohol	Conf.	67-56-1	OSHA TWA 200PPM PEL ACGIH TWA 200PPM ACGIH STEL 250 PPM
Formaldehyde	Conf.	50-00-0	ACGIH TLV 0.3PPM, OSHA PEL 0.75PPM,TWA 2PPM(25mg/m3) 15min. STEL

SECTION III – PHYSICAL DATA

APPEARANCE.....Clear colorless liquid
BOILING POINT..... 760 mm Hg approx. 100 C.
FREEZING POINT.....ND
VAPOR PRESSURE.....@ 25 C. approx. 40mm Hg @ 39 C.

Material Safety Data Sheet

HORIZON-SPT

SPECIFIC GRAVITY.....1.084 – 1.087
Ph.....3.0 to 4.5
SOLUBILITY IN WATER.....Infinite

SECTION IV – FIRE AND EXPLOSION DATA

FLASHPOINT.....144 DEGR. F.
EXTINGUISHING MEDIA.....”ALCOHOL FOAM”, DRY POWDER
CARBON DIOXIDE (CO2).
UNUSUAL FIRE HAZARD.....None

SECTION V – REACTIVITY DATA

STABILITY.....Normally stable, but may further react at
high temperatures to form methanol, formic
acid or methylals.
INCOMPATIBILITY.....Oxidizing Materials.
DECOMPOSITION PRODUCTS.....From fire: Smoke, Carbon Dioxide, Carbon
Monoxide.
HAZARDOUS POLYMERIZATION...Will not occur.

SECTION VI – HEALTH DATA

EYES.....Chemical goggles
SKIN(DERMAL).....Irritant
OVEREXPOSURE EFFECTS...Skin irritation develops slowly after contact. Eye
irritation develops immediately upon contact.
Overexposure: Irritation of Respiratory Tract,
Nervous System Depression, Headaches, Dizziness,
Staggering Gait, Confusion, Unconsciousness,
Coma.
FIRST AID PROCEDURES.....In case of eye contact, flush immediately with

Material Safety Data Sheet

HORIZON-SPT

plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If inhaled, remove to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen. Get medical attention. If swallowed, induce vomiting immediately by giving two glasses of water and sticking finger down throat. Never give anything by mouth to an unconscious person.

SECTION VII – EMPLOYEE PROTECTION

RESPIRATORY PROTECTION...NOISH approved Organic Vapor Mask recommended if TLV is exceeded.
VENTILATION.....Desired in closed places
MECHANICAL EXHAUST.....Desired
LOCAL EXHAUST.....Desired in closed places.
PROTECTIVE GLOVES.....Chemical type suitable for alcohol solvents.
EYE PROTECTION.....Chemical goggles or full face shield recommended.
PROTECTIVE EQUIPMENT.....HMIS Personal Protection: B: Safety glasses and gloves.

SECTION VIII – SPILL AND DISPOSAL DATA

FOR SPILL.....In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations.
WASTE DISPOSAL.....Hazardous waste. EPA approved hazardous waste disposal site. Follow applicable local, state and federal regulations.

SECTION IX – TRANSPORTATION DATA

PROPER SHIPPING NAME.....Formaldehyde, Solutions, 8, UN2209, PG III, Guide 132.

**Material Safety Data Sheet
HORIZON-SPT**

HAZARD CLASS AND LABEL...Corrosive
UN NUMBER.....2209
REPORTABLE QUANTITY.....20,000 pounds based on Methanol

SECTION X – SARA TITLE III, SECTION 313

TOXIC CHEMICALS	PERCENT	PROD CAS NUMBER
Methyl Alcohol	11	67-56-1
Formaldehyde	37	50-00-0

SECTION XI – ENVIRONMENTAL DATA

CLEAN WATER ACT.....CWA SECTION 311
SDWA OF 1986
SDWA (52 FR25690, JULY 8, 1987)
CLEAN AIR ACT.....CAA SECTION 111
EPA HAZARD.....ACUTE, CHRONIC, FIRE
CERCLA RQ VALUE.....Methanol – 5000#/percentage in formula
SARA TPQ.....NONE
SARA RQ.....5000 pounds based on Methanol
RCRA HAZARDOUS WASTE...U154 – Methanol