Material Safety Data Sheet



Date of issue

7 February 2012

Version

1

Product and company identification

Product name

: PELS™ Caustic Soda Beads

Code

- 0040

Synonym

: Sodium Hydroxide; Anhydrous Sodium Hydroxide, Caustic Soda; NaOH

Supplier

: PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272

Emergency telephone

: (412) 434-4515 (U.S.)

number

(514) 645-1320 (Canada) 01-800-00-21-400 (Mexico)

Technical Phone Number

: 1-800-243-6774 (C/A) 8am-5pm Eastern time

2. Hazards identification

Emergency overview

: DANGER!

HARMFUL OR FATAL IF SWALLOWED. CAUSES SEVERE EYE AND SKIN BURNS. CAUSES RESPIRATORY TRACT IRRITATION. HARMFUL IF INHALED. MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA. Add this product only to water. Never add water to this product. Do not add to warm or hot water, a violent eruption or explosive reaction can result. Avoid contact with organic materials. Take any precaution to avoid mixing with strong acids. May cause fire or explosion.

Do not swallow. Do not get in eyes or on skin or clothing. Do not breathe dust or mists from solutions. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.

Potential acute health effects

Inhalation

: Harmful if inhaled. Causes burns. Corrosive to the respiratory system.

Ingestion

: Harmful or fatal if swallowed. May cause burns to mouth, throat and stomach.

Skin

: Severely corrosive to the skin. Causes severe burns.

Eyes

Severely corrosive to the eyes. Causes severe burns. Direct contact with the eyes can

cause irreversible damage, including blindness.

Over-exposure signs/symptoms

Inhalation

: Adverse symptoms may include the following:

Respiratory tract irritation

coughing Edema

Ingestion

: Adverse symptoms may include the following:

stomach pains nausea or vomiting gastric perforation blistering may occur

Skin

: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

ulcerations

Eyes

.

United States - Canada - Mexico

Page: 1/8



Product code 0040

Date of issue 7 February 2012 Version 1

Product name PELS™ Caustic Soda Beads

2. Hazards identification

Adverse symptoms may include the following:

pain watering redness Cornea opacity ulcerations

Direct contact with the eyes can cause irreversible damage, including blindness.

Medical conditions aggravated by overexposure : Pre-existing disorders involving any target organs mentioned in this MSDS as being at

risk may be aggravated by over-exposure to this product.

This Material Safety Data Sheet has been prepared in accordance with Canada's Workplace Hazardous Materials Information System (WHMIS) and the OSHA Hazard Communication Standard (29 CFR 1910.1200).

See toxicological information (Section 11)

3. Composition/information on ingredients

<u>Name</u>	<u>CAS number</u>	<u>%</u>	
sodium hydroxide	1310-73-2	96 - 100	
sodium chloride	7647-14-5	0 - 2	
sodium carbonate	497-19-8	0 - 2	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Material Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Eye contact : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek immediate medical attention.

: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with

water or use recognized skin cleanser.

: Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

Ingestion : If swallowed, seek medical advice immediately and show this container or label.

Keep person warm and at rest. Do not induce vomiting.

Notes to physician : No specific treatment. Treat symptomatically. Contact poison treatment specialist

immediately if large quantities have been ingested or inhaled.

5. Fire-fighting measures

Flammability of the product : Attacks many metals producing extremely flammable hydrogen gas which can form explosive mixtures with air.

Extinguishing media

Inhalation

Suitable : Use an extinguishing agent suitable for the surrounding fire.

Not suitable : None known.

Special exposure hazards : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable

training.

Hazardous combustion products

:

United States - Canada - Mexico

Page: 2/8



MATERIAL SAFETY DATA SHEET CUST:CHEM STATION

MSDS NO PG0040 VERSION:029 06/26/12

Product code 0040

Date of issue 7 February 2012 Version 1

Product name PELS™ Caustic Soda Beads

5. Fire-fighting measures

Decomposition products may include the following materials:

carbon oxides

halogenated compounds metal oxide/oxides

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions : No action shall be taken involving any personal risk or without suitable training.

Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal

protective equipment.

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains

and sewers. Inform the relevant authorities if the product has caused environmental

pollution (sewers, waterways, soil or air).

Large spill : Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste

disposal contractor. Note: see section 1 for emergency contact information and section

13 for waste disposal.

Small spill : Move containers from spill area. Vacuum or sweep up material and place in a

designated, labeled waste container. Dispose of via a licensed waste disposal

contractor.

Special provisions : If mixed with water, or likely to become mixed with water or any liquid, dike area to contain spill. Recycle, if possible. Or, dilute spill with large amounts of water then

neutralize with dilute acid. Dispose of contents and container in accordance with all local, regional, national and international regulations. After all visible traces have been

removed, flush area with large amounts of water.

Reference to other sections : See Section 1 for emergency contact information.

See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

7. Handling and storage

Handling

Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Do not swallow. Do not get in eyes or on skin or clothing. Do not breathe dust or mists from solutions. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Add this product only to water. Never add water to this product. Do not add to warm or hot water, a violent eruption or explosive reaction can result. May cause fire or explosion. Avoid contact with organic materials. Take any precaution to avoid mixing with strong acids. When making solutions or diluting, only add caustic soda slowly to surface of cold water while stirring. Attacks many metals producing extremely flammable hydrogen gas which can form explosive mixtures with air. Caustic soda may react with various sugars to generate carbon monoxide. Hazardous carbon monoxide gas can form upon contact with food and beverage products in enclosed vessels and can cause death. Empty containers retain product residue and can be hazardous. Do not reuse container.

Storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. Do not enter a storage tank or container (truck or rail) that has contained this product, even if it appears empty.

United States - Canada - Mexico

Page: 3/8



Product code 0040

Date of issue 7 February 2012 Version 1

Product name PELS™ Caustic Soda Beads

7. Handling and storage

8. Exposure controls/personal protection

Name	Result	ACGIH	OSHA	Ontario	Mexico	PPG
sodium hydroxide	TWA	Not established	2 mg/m³	Not established	Not established	Not established
	STEL	2 mg/m³ C	Not established	2 mg/m³ C	2 mg/m³ C	Not established

Key to abbreviations

Α	= Acceptable Maximum Peak	S	=	Potential skin absorption
ACGIH	= American Conference of Governmental Industrial Hygienists.	SR	=	Respiratory sensitization
С	= Ceiling Limit	SS	=	Skin sensitization
F	= Fume	STEL	=	Short term Exposure limit values
IPEL	= Internal Permissible Exposure Limit	TD	=	Total dust
OSHA	= Occupational Safety and Health Administration.	TLV	=	Threshold Limit Value
R	= Respirable	TWA	=	Time Weighted Average
Z	= OSHA 29CFR 1910.1200 Subpart Z - Toxic and Hazardous Substances			

Consult local authorities for acceptable exposure limits.

Recommended	monitoring
procedures	

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Engineering measures

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal protection

Eyes Hands : Chemical splash goggles and face shield.

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Gloves Respiratory : Impervious gloves. nitrile, neoprene

: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Skin

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

MATERIAL SAFETY DATA SHEET CUST: CHEM STATION

MSDS NO:PG0040 VERSION:029 06/26/12

Product code 0040

Date of issue 7 February 2012 Version 1

Product name PELS™ Caustic Soda Beads

Physical and chemical properties 9.

Physical state

: Solid. [Dustless granules.]

Flash point

Closed cup: Not applicable. [Product does not sustain combustion.]

Color Odor

: White. Odorless.

Hq

: Strongly basic

Melting/freezing point

Boiling/condensation point : 1390°C (2534°F) : 310 to 320°C (590 to 608°F)

Specific gravity Density (Ibs / gal) : 17.78

Bulk Density (g/cm³)

: 1.12 (loosely packed)

: Not applicable. Vapor pressure Vapor density : Not applicable Volatility : 0% (w/w) Evaporation rate

Viscosity

: Not applicable. : Not applicable.

Solubility

: Easily soluble in the following materials: cold water.

Water Solubility at room

temperature

: 3470 g/l @ 100°C

Partition coefficient: n-

octanol/water

: Not available.

% Solid. (w/w)

: 100

10 . Stability and reactivity

Stability

Conditions to avoid

Materials to avoid

- : Stable under recommended storage and handling conditions (see section 7).
- Avoid increased storage temperature. Pressure hazard
- Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.

Reactive or incompatible with the following materials: metals (Attacks many metals producing extremely flammable hydrogen gas which can form explosive mixtures with air.), acids, organic materials (May cause fire or explosion.), food sugars (Caustic soda may react with various sugars to generate carbon monoxide.), water (Aqueous reaction with caustic soda can generate heat (strongly exothermic).)

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Possibility of hazardous

: Under normal conditions of storage and use, hazardous reactions will not occur.

reactions

11. Toxicological information

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
sodium hydroxide	LD50 Oral	Rat	0.24 g/kg	-
sodium chloride	LD50 Oral	Rat	3000 mg/kg	-
sodium carbonate	LD50 Oral	Rat	4090 mg/kg	-

Conclusion/Summary **Chronic toxicity**

: Harmful or fatal if swallowed. Harmful if inhaled.

Conclusion/Summary

: Not available.

Irritation/Corrosion

United States - Canada - Mexico

Page: 5/8



MATERIAL SAFETY DATA SHEET CUST: CHEM STATION

MSDS NO PG0040 VERSION:029 06/26/12

Product code 0040

Date of issue 7 February 2012 Version 1

Product name PELS™ Caustic Soda Beads

11. Toxicological information

Skin

: Severely corrosive to the skin. Causes severe burns.

Eyes

: Severely corrosive to the eyes. Causes severe burns. Direct contact with the eyes can cause irreversible damage, including blindness.

_ . .

Respiratory Sensitization : Corrosive to the respiratory system.

Skin Respiratory : Not available. : Not available.

Target organs

: May cause damage to the following organs: lungs, gastrointestinal tract, upper

respiratory tract, skin, eyes.

Contains material which may cause damage to the following organs: eye, lens or cornea,

stomach.

Carcinogenicity

Carcinogenicity

: No known significant effects or critical hazards.

<u>Mutagenicity</u>

Mutagenicity

: No known significant effects or critical hazards.

Teratogenicity

Teratogenicity

: No known significant effects or critical hazards.

Reproductive toxicity

Developmental effects

: No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

12. Ecological information

Environmental effects

: No known significant effects or critical hazards.

Aquatic ecotoxicity

Product/ingredient	Result	Species	Exposure
name			
sodium hydroxide	Acute LC50 196 mg/L Marine water	Fish - Guppy - Poecilia reticulata	96 hours
	Chronic NOEC 56 mg/L Marine water	Fish - Guppy - Poecilia reticulata	96 hours
sodium chloride	Acute LC50 1294600 ug/L Fresh water	Fish - Bluegill - Lepomis macrochirus	96 hours
	Acute EC50 402600 to 469200 ug/L Fresh water	Daphnia - Water flea - Daphnia magna	48 hours
	Chronic NEL 0.86 g/L Fresh water	Fish - Fathead minnow - Pimephales promelas	96 hours
sodium carbonate	Acute LC50 300000 ug/L Fresh water	Fish - Bluegill - Lepomis macrochirus	96 hours
	Acute LC50 265000 ug/L Fresh water	Daphnia - Water flea - Daphnia magna	48 hours

Conclusion/Summary

: Harmful to aquatic life.

13. Disposal considerations

Waste disposal

: The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled

United States - Canada - Mexico

Page: 6/8



MATERIAL SAFETY DATA SHEET CUST: CHEM STATION

MSDS NO:PG0040 VERSION:029 06/26/12

Product code 0040

Date of issue 7 February 2012 Version 1

Product name PELS™ Caustic Soda Beads

13. Disposal considerations

material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

14. Transport information

rmation	Additional information	PG*	Classes	Proper shipping name	UN number	Regulation
	-	ll l	8	SODIUM HYDROXIDE, SOLID	1823	UN
	-	II	8	SODIUM HYDROXIDE, SOLID	1823	IMDG
	-	II	8	SODIUM HYDROXIDE, SOLID	1823	DOT
	-	II	8	SODIUM HYDROXIDE, SOLID	1823	DOT

PG*: Packing group

Reportable quantity RQ : CERCLA: Hazardous substances.: sodium hydroxide: 1000 lbs. (454 kg);

15. Regulatory information

United States inventory (TSCA 8b) : All components are listed or exempted.

Australia inventory (AICS) : All components are listed or exempted.

Canada inventory (DSL) : All components are listed or exempted.

China inventory (IECSC) : All components are listed or exempted.

Europe inventory (REACH) : Please contact your supplier for information on the inventory status of this material.

Japan inventory (ENCS) : All components are listed or exempted.

Korea inventory (KECI) : All components are listed or exempted.

New Zealand (NZIoC) : All components are listed or exempted.

Philippines inventory (PICCS) : All components are listed or exempted.

United States

SARA 302/304/311/312 extremely hazardous substances: No products were found. SARA 302/304 emergency planning and notification: No products were found.

SARA 302/304/311/312 hazardous chemicals: sodium hydroxide; sodium carbonate; sodium chloride

CERCLA: Hazardous substances.: sodium hydroxide: 1000 lbs. (454 kg);

SARA 311/312 MSDS Distribution - Chemical Inventory - Hazard Identification:

Chemical name	CAS#	<u>Acute</u>	Chronic	<u>Fire</u>	<u>Reactive</u>	<u>Pressure</u>
sodium hydroxide	1310-73-2	Υ	N	N	Υ	N
sodium chloride	7647-14-5	N	N	N	N	N
sodium carbonate	497-19-8	Y	N	N	Υ	N
	Product as-supplied :	Υ	N	N	Υ	N

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

Canada

WHMIS (Canada)

: Class E: Corrosive solid. Class D-1B: Material causing immediate and serious toxic

effects (Toxic). Class D-2B: Material causing other toxic effects (Toxic).

Mexico

Classification

Flammability: 0 Health: 3 Reactivity: 1

United States - Canada - Mexico

Page: 7/8



ORDER NO:AL254245

MATERIAL SAFETY DATA SHEET CUST:CHEM STATION

MSDS NO:PG0040 VERSION:029 06/26/12

Product code 0040

Date of issue 7 February 2012 Version 1

Product name PELS™ Caustic Soda Beads

16. Other information

Hazardous Material Information System (U.S.A.)

Health: 3

Flammability: 0 Physical hazards:

(*) - Chronic

effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)

Health: 3

Flammability: 0

Instability : 1

instability :

Other special considerations

: NSF/ANSI Drinking Water Treatment Chemicals - Health Effects Listing - PPG Pels™ Caustic Soda Beads are certified for maximum use at 100 mg/L under NSF/ANSI

Standard 60.

Other information

: PELS™ is a trademark of PPG Industries Ohio. Inc.

Date of previous issue

: No previous validation.

Organization that prepared

: EHS

the MSDS

 \overline{V} Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

