


Integrity Industries, Inc.
P. O. Box 5342

Kingsville
361-595-5561
361-595-5588

TX 78363



Material Safety Data Sheet


Page 1

	SECTION 1.0
Revised Date	02/11/02
Supercedes	12/04/98
	SECTION 2.0
Trade Name	ULTRA LUBE D
Synonyms/Other Designations	ULTRA LUBE D
Chemical Formula	Drilling lubricant
Hazard(s)	Contains petroleum distillates
	SECTION 3.0
Boiling Point	N/A
Freezing Point	N/A
Specific Gravity	0.88
Vapor Pressure (mm Hg)	N/A
Vapor Density	<1.0
Solubility in H2O	Insoluble
Appearance	Brown liquid
Odor	Solvent
	SECTION 4.0
Stability	Stable
Incompatibility	High heat, sparks, open flames
Hazardous Decomposition Products	Combustion may produce smoke and carbon oxides
Hazardous Polymerizations	Will not occur
	SECTION 5.0
Flash Point	140 F
Extinguishing Media	Water, Dry Chemical, Foam, CO2
Special Fire Fighting Procedures	Normal firefighting procedures
Unusual Fire Hazards	Excessive ambient temperature may cause sealed containers to explode; Treat as petroleum distillate.
pH	N/A
	SECTION 6.0
Inhalation	Move to well ventilated area; if breathing difficulties persist after 15 minutes, seek medical help
Eye Contact	Wash eye thoroughly for 15 minutes; if irritation persists, seek medical help.
Skin Contact	Wash exposed area with soap & water; if irritation persists, seek medical help.
Ingestion	Do not induce vomiting; seek medical assistance

Integrity Industries, Inc.
P. O. Box 5342

Kingsville
361-595-5561
361-595-5588

TX 78363



4079 ULTRA LUBE D

Material Safety Data Sheet

	SECTION 7.0
Acute	Contains petroleum distillates which may irritate mucous, stomach, and respiratory tract, producing symptoms such as headaches, dizziness, nausea, and vomiting
Chronic	Contains petroleum distillates which may produce dermatitis from prolonged or repeated skin contact.
	SECTION 8.0
Accidental Spill Procedures	Berm spill area and pump out for reuse. Absorb residue with inert material and dispose of according to local, state, and federal regulations.
Handling & Storage	Observe normal handling and storage procedures
	SECTION 9.0
Respiratory Protection	NIOSH approved organic vapor filter respirator in confined areas
Ventilation	Desired
Exhaust	Mechanical
Protective Gloves	Rubber gloves
Eye Protection	Safety Glasses, Goggles, face shield
Other Protection	Eye wash/Safety shower
	SECTION. 10.0
DOT Proper Shipping Name	Combustible Liquid n.o.s. (contains petroleum distillates)
DOT Hazard Class or Division	Combustible Liquid
DOT Identification Number	NA 1993
DOT Packaging Group	III
Type Label(s) Required or Exemption Nu	None For Limited Quantity requirement see DOT Regulation 49 CFR.
	SECTION. 11.0
DISCLAIMER	SOME INFORMATION PROVIDED HEREIN WAS DRAWN FROM SOURCES OTHER THAN INTEGRITY INDUSTRIES.
DISCLAIMER	THE INFORMATION PROVIDED HEREIN IS BELIEVED BY INTEGRITY INDUSTRIES TO BE CORRECT AND RELIABLE; NO EXPRESSED OR IMPLIED WARRANTY IS PROVIDED HOWEVER.
DISCLAIMER	INTEGRITY INDUSTRIES ASSUMES NO RESPONSIBILITY AND DENIES ALL LIABILITY FOR ANY LOSS, DAMAGE, OR EXPENSE CONNECTED WITH CUSTOMERS' METHOD OF HANDLING, STORAGE, USE, AND DISPOSAL OF THIS PRODUCT.
DISCLAIMER	THE MSDS INFORMATION PROVIDED HEREIN IS APPLICABLE ONLY TO THIS PRODUCT.